

Amplifiers

Model 500S1G2z5A

Features:

- 500 W CW, 1.0 – 2.5 GHz
- 100% mismatch tolerant
- Built-in fault monitoring, logging and protection
- Touch screen display
- Remote control: Ethernet, USB, GPIB, fiber-optic serial, RS-232
- Modular design for easy maintenance and service
- Low acoustical noise

Applications:

- EMC (military, aviation, automotive, commercial)
- Radiated and conducted EMC testing
- General purpose, antenna, and component testing
- 4G LTE, 5G NR (FR1/FR2), OFDM, PSK/QAM, Wi-Fi etc.

To view our full amplifier portfolio visit:
www.ar.ametek-cts.com

AR RF/Microwave Instrumentation
160 Schoolhouse Rd
Souderton, PA 18964
215.723.8181
ISO 9001: 2015 Certified
ISO 17025 :2017 Accredited

The Model 500S1G2z5A is a self-contained, air-cooled, solid-state Class A broadband power amplifier designed for applications demanding wide bandwidth coverage, high gain, and linear performance. It delivers a minimum of 500 W over a frequency range of 1.0 to 2.5 GHz. The unit includes safeguards against input overdrive beyond 0 dBm, as well as various fault conditions such as excessive temperature and power supply issues.

A scalable, module-based design combined with advanced forced air cooling ensures reliable operation and long-term performance in demanding test environments. A clear front panel display provides immediate visibility of operating status and fault conditions, enabling fast setup and confident operation. For maximum flexibility, all control and monitoring functions can be accessed either locally via the front panel or remotely through a wide range of standard interfaces, including GPIB/IEEE 488, RS 232, fiber optic serial, USB, and Ethernet.

This Class A amplifier is engineered for EMC immunity, communications, and aerospace & defense testing, delivering exceptional stability and linearity under demanding load conditions, including high VSWR, open, or short circuits. Low spurious emissions, high spectral purity, and wideband performance make it ideal for modern wireless and 5G applications.

Export classification for this device is EAR99. These goods, technologies, or software are regulated under U.S. Export Administration Regulations, and unauthorized diversion is prohibited by U.S. law.



- 500 W
- 1.0 – 2.5 GHz

Electrical Specifications					
Parameter	Symbol	Minimum	Typical	Maximum	Unit
Rated Power Output	PSAT	500	550	>600	W
Input for Rated Output	Pin			1.0	mW
				0	dBm
Power Output @ 3 dB Compression	P3dB	450	550	>580	W
Power Output @ 1 dB Compression	P1dB	350	400	>450	W
Operating Frequency	BW	1.0		2.5	GHz
Gain (Small Signal)		57			dB
Gain Reduction Adjustment (when below compression)		20			dB
Flatness	ΔG		±1.5	±2.0	dB
Input Impedance	Z in		50		Ohm
			2.0:1		VSWR
Output Impedance	Z out		50		Ohm
3 rd Order Intercept	IP3		+66		dBm
Noise Figure	NF		10		dB
Harmonic Distortion @ 350 W	H2, H3			-20	dBc
Harmonic Distortion @ 500 W	H2, H3		-20		dBc
Spurious			-73		dBc
Power Consumption	P _D			2250	W

Absolute Maximum Rating

Exceeding any of the limits listed here may result in permanent damage to the device.

Parameter	Minimum	Typical	Maximum	Unit
RF Drive		0	+13	dBm
RF Load		1:1	∞	VSWR
RF Load Reflected Will operate without damage or oscillation when connected to any load impedance without the aid of foldback circuitry.			25	%
AC Power (single phase)	100		240	VAC
	47	60	63	Hz
Ambient Temperature	+5	+25	+40	°C
Storage Temperature	-20		+50	°C
Altitude			2000	m
Shock/Vibration	Normal Truck Transport			

Model 500S1G2z5A

- 500 W
- 1.0 – 2.5 GHz



Mechanical Specifications		
Parameters	Typical	Unit
Dimensions (With Cabinet) (W x H x D)	50.3 x 37.3 x 74.9	cm
	19.8 x 14.7 x 29.5	in
Dimensions (No Cabinet) – 8U for 19" Rack	48.3 x 35.5 x 74.9	cm
	19 x 14.0 x 29.5	in
Weight (With Cabinet)	64.9	kg
	143	lb
Weight (No Cabinet)	50.3	kg
	111	lb
Cooling	Forced air (self-contained fans)	
Acoustic Noise Measured @ 1 Meter	56	dBA

Connector Interfaces	
Function	Type
RF Input	N, female, rear (50 Ω) (option front)
RF Output	7/16 DIN, female, rear (50 Ω) (option front)
IEEE-488	24-pin
RS-232	9 pin subminiature D
Ethernet	RJ-45
RS-232 (fiber optic)	ST
USB 2.0	Type B
Interlock	15-pin subminiature D

Regulatory Compliance	
Type	Standard
EMC	EN 61326-1
Safety	UL 61010-1
	CAN/CSA C22.2 #61010-1
	CENELEC EN 61010-1
RoHS	Directive 2011/65/EU
Export	EAR99

Ordering Options

500S1G2z5A - **N** - **716** - **Enclosure**
 Model RF IN Conn RF OUT Conn No Enclosure
 Location, Type Location, Type

Connector	
Front	F
Rear	R

Enclosure	
Enclosure	E
No Enclosure	NE




Model 500S1G2z5A

- 500 W
- 1.0 – 2.5 GHz




Envelope Drawing




- 500 W
- 1.0 – 2.5 GHz

TYPICAL OUTPUT POWER




TYPICAL SMALL SIGNAL GAIN @ -20dBm INPUT




- 500 W
- 1.0 – 2.5 GHz

TYPICAL HARMONICS @ 350 WATTS



TYPICAL NOISE FIGURE



- 500 W
- 1.0 – 2.5 GHz

TYPICAL INPUT VSWR

